

High Efficient LED Floodlight

LightPartner®

ST76M



HIGH EFFICIENT, STAINLESS STEEL LED FLOODLIGHT FOR DECKS, HOLDS, INDUSTRIAL AREAS

■ PART NO.

ST76 M 2x 22°	5101005810-001
ST76 M 2x 37°	5101005810-000
ST 76 M 2x 52°	5101005810-002
ST76 M 2x 91°	5101005810-027

🔧 SPARE PARTS

PART NO.

Cover with frame	7902003800
Bracket	7501000300
Reflector kit 22°	7901003400
Reflector kit 37°	7901003500
Reflector kit 52°	7901003600
Reflector kit 92°	7901003700

★ EXTRAS

- > 24 V DC execution
- > Different cable glands
- > Reflectors with different beam angles can be combined
- > Different color temperatures

Design	According to rules of maritime classification societies and relevant standards
Housing	Stainless steel, 1.4404 (AISI 316L), seamless deep drawn powder coated white (RAL9016)
Safety pane	Tempered glass, DIN 12150, partially lacquered
Mounting	Stainless steel bracket, adjustable
Cable entry	Exterior connection box, cable gland M20
Protection class	IP67
Weight	7.5 kg
Light source	2x LED array
Wattage	2x 25 W
CCT (color)	5,700 K
Luminous flux	6,000 lm
CRI	≥ 80
Voltage	110-240 V AC
Frequency	50-60 Hz

