

High Efficient LED Floodlight

ST76XL

LightPartner®



HIGH EFFICIENT, STAINLESS STEEL LED
FLOODLIGHT FOR DECKS, HOLDS,
INDUSTRIAL AREAS

■ PART NO.

ST76 XL 4x 22°	5101005510-000
ST76 XL 4x 37°	5101005510-001
ST76 XL 4x 52°	5101005510-002
ST76 XL 4x 91°	5101005510-005

🔧 SPARE PARTS

PART NO.

Cover with frame	7902003400
Bracket	7501006200
Reflector kit 22°	7901003400
Reflector kit 37°	7901003500
Reflector kit 52°	7901003600
Reflector kit 92°	7901003700

★ EXTRAS

- > 24 V DC execution
- > Different cable glands
- > Reflectors with different beam angles can be combined
- > Different color temperatures

Design	According to rules of maritime classification societies and relevant standards
Housing	Stainless steel, 1.4404 (AISI 316L), seamless deep drawn powder coated white (RAL9016)
Safety pane	Tempered glass, DIN 12150, partially lacquered
Mounting	Stainless steel bracket, adjustable
Cable entry	Exterior connection box, cable gland M20
Protection class	IP67
Weight	16,5 kg
Light source	4x LED array
Wattage	4x 25 W
CCT (color)	5,700 K
Luminous flux	11,000 lm
CRI	≥ 80
Voltage	110-240 V AC
Frequency	50-60 Hz

