

**Ballast Unit For ST76
Floodlight**



VG76



BALLAST UNIT FOR ST76 FLOODLIGHTS WITH HIGH PRESSURE DISCHARGE LAMPS

■ 1x 250 W		PART NO.
Type	Weight	
50 Hz	10.8 kg	5801000100
60 Hz	10.8 kg	5801000100-001

■ 2x 250 W		PART NO.
Type	Weight	
50 Hz	18.8 kg	5801000200
60 Hz	18.8 kg	5801000200-001

■ 1x 400 W		PART NO.
Type	Weight	
50 Hz	10.8 kg	5801000300-000
60 Hz	10.8 kg	5801000300-001

■ 2x 400 W		PART NO.
Type	Weight	
50 Hz	18.8 kg	5801000400
60 Hz	18.8 kg	5801000400-001

■ 1x 1000 W		PART NO.
Type	Weight	
50 Hz	15.8 kg	5801000500
60 Hz	15.8 kg	5801000500-001

Design	According to rules of maritime classification societies and relevant standards
Housing	Stainless steel, 1.4404 (AISI 316L), powder coated white (RAL9016)
Mounting	Mounting holes, Ø 10 mm
Cable entry	Max. 4 cable glands M24, brass with earthing insert
Ballast	Electromagnetic ballast with capacitor
Protection class	IP67
Voltage	230 V AC
Frequency	50 Hz or 60 Hz

🔧 SPARE PARTS	PART NO.
Clamps (6 pcs)	7106000700

- ★ EXTRAS
- > 120 V AC execution
 - > Different cable glands

