

**CORNICE LUMINAIRE, EFFICIENT LIGHTING FOR FLOOR AREAS,  
PASSAGE WAYS, CABINS AND ACCOMODATION AREAS**



# EL33



CORNICE LUMINAIRE, EFFICIENT LIGHTING FOR FLOOR AREAS, PASSAGE WAYS, CABINS AND ACCOMODATION AREAS

<b>Design</b>	According to rules of maritime classification societies and relevant standards
<b>Housing</b>	Galvanized steel, powder coated white (RAL9016)
<b>End caps</b>	Polycarbonate, white
<b>Diffuser</b>	Polycarbonate, opal or crystal
<b>Mounting</b>	4 mounting holes, Ø 5.4 mm
<b>Cable entry</b>	2 / 4 inlets for cables max. Ø 11 mm
<b>Protection class</b>	IP30
<b>Voltage</b>	220-240 V AC
<b>Frequency</b>	50-60 Hz

### LED SOLUTION

EL33S (max. 10 W)	5113003100-xxx
EL33S (max. 20 W)	5113003200-xxx
Light source	Linear LP LED module
Weight	2.8 kg (1x 10 W) 3.0 kg (1x 20 W)
Wattage	Max.10 W / max. 20 W
CCT (color)	3,000 K or 4,000 K
CRI	≥ 80
Luminous flux	1,300 lm (10 W) 3,000 lm (20 W)

### FLUORESCENT SOLUTION

EL33 1x 18 W	5113000100-014
EL33 2x 18 W	5113000400-005
Light source	T8 fluorescent tubes (not included)
Lamp base	G13
Wattage	1x / 2x 18 W

### SPARE PARTS

### PART NO.

Opal cover	7112006900
Crystal cover	7112006800
End cap	7503000300

### ★ EXTRAS

- > 120 V AC execution
- > 1x / 2x 36 W T8 execution
- > With 2-pole-switch
- > Max. 10 W execution with battery back-up

