

MULTIPURPOSE WATERTIGHT LUMINAIRE FOR DECKS, STORES, ENGINE ROOMS



TL09



MULTIPURPOSE WATERTIGHT LUMINAIRE FOR DECKS, STORES, ENGINE ROOMS

Design	According to rules of maritime classification societies and relevant standards
Housing	Galvanized steel, powder coated white (RAL9016)
Cover	LED: Opal polycarbonate, Fluorescent: Satin polycarbonate, impact-proof, UV resistant
Mounting	2 mounting holes, Ø 9 mm
Cable entry	2 cable glands M20, LED: nickel plated brass, Fluorescent: PA 6
Protection class	IP67
Voltage	220-240 V AC
Frequency	50-60 Hz

LED SOLUTION

TL09	5105009800-004
Light source	LED module
Weight	1.5 kg
Wattage	Max. 4 W
CCT (color)	4,000 K
CRI	≥ 80

FLUORESCENT SOLUTION

TL09	5105009300-002
Light source	Compact fluorescent lamp (not included)
Lamp base	2G7
Weight	1.6 kg
Wattage	1x 9 W

SPARE PARTS

PART NO.

Opal cover	7925000800
Satin cover	7925000900
Lamp holder 2G7	7111022100

EXTRAS

- > Stainless steel housing
- > Emergency battery back-up
- > Different cable glands
- > 120 V AC execution

