




Bed Side Lamp DM-ZYT08







The scope of application:

The products are designed as bedside lamp to use at the living room in ship cabin.

Products feature:

- 1.The shell of light is made of good quality cold rolled steel sheets by compression molding.
- 2. The shade of light adopt the figure oral poly carbonate injection molding.
- 3. This light can be equipped with switch and socket device.
- 4. The cable outside diameteris & 6-& 8 mm.


Adopt standard and products certification:

- 1.Conform to STANDARD of IEC60598-1-2008.
- 2.Conform to RULES FOR CLASSIFICATION OF SEA-GOING STEEL SHIPS.
- 3. Approved by CHINA CLASSIFICATION SOCIETY(CCS).
- 4. Passed the EUROPEAN UNION (CE) CERTIFICATION

TYPE	VOLT	WATTS	L(mm)	L1(mm)	LAMP HOLDER	WEIGHT	PROTECTION CLASS	DM CODE
ом-гутрв	AC110V	8W	347	194	G5	0.92kg	IP34	DM-ZYT081116
	AC220V							DM-ZYT081226

LED Bed Side Lamp DM-ZYT08-1LED





The scope of application

This product is designed as bedside lamp to use at the living room in ship cabin.

Products feature:

- 1. The shell of light is made of good quality cold rolled steel sheets by compression molding, which surface was powder coated and processed by white acid epoxy polyester powder.
- 2. The shade is made of milky poly carbonate by injection molding, with light softness.
- 3.LED light source, long working life, high light intensity, low energy consumption.
- 4. The shade and shell are fixed by ABS end plate and screws, elegant appearance, convenient dis-assembly, easy to maintain.
- 5.The diameter of cable is &6 ~ &8mm.

Adopt standard and products certification:

- 1. Conform to Rules for the classification of sea-going steel
- 2.Conform to STANDARD of IEC60598-1-2008.
- Approved by CHINA CLASSIFICATION SOCIETY(CCS).

TYPE	VOLT	WATTS	L(mm)	L1(mm)	LAMP HOLDER	WEIGHT	PROTECTION CLASS	DM CODE
DM-ZYT08-1LED	AC110V	3W	347	194		0.92kg	IP34	DM-ZYT08LEDA
	AC220V							DM-ZYT08LED

P.O Box: 232974, Dubai, United Arab Emirates. E-mail: info@dreammarine.ae Web: www.dreammarine.ae Tel: +971 4 5578346 Fax: +971 4 5578343,