

HF-CXOSA 0.6/1kV

Halogen free low smoke power cables,
with copper wire braiding



Type Approval Certificates

- American Bureau of Shipping
- Bureau Veritas
- China Classification Society
- Det Norske Veritas
- Germanischer Lloyd
- Korean Register
- Lloyd's Register
- Nippon Kaiji Kyokai
- Registro Italiano Navale

Application

For fixed installations in all areas and open deck



Conductors

- acc. to IEC 60228 - Class 2 circular stranded copper for size 10mm² and below
- Class 5 flexible conductor for size 16mm² and above

Insulation

cross-linked polyethylene HF XLPE-90°C acc. to IEC 60092-351

Filler

polypropylene yarn

Inner Covering

polyester tape

Screen/Armour

copper wire braiding as armour and shielding to achieve better EMI (Electro Magnetic Interference) performance

Outer Sheath

thermoplastic polyolefine halogen-free compound type SHF1 acc. to IEC 60092-359

Color of Outer Sheath

black

Core Identification

- 1-core : not specified
- 2-core : brown, blue
- 3-core : black, brown, grey
- 4-core : black, blue, brown, grey
- 5-core : grey, black₁, blue, brown, black₂
- 6-core : white with black numbering
- and more

Maximum conductor operating temperature	: +90°C
Lowest ambient temperature for fixed installation	: -40°C
Lowest installation temperature	: -15°C
Maximum short-circuit conductor temperature	: +250°C
Minimum bending radius	: 6D (D is the overall diameter of the cable)

Test Performances

Flame retardant	: IEC 60332-3-22 Category A
Smoke emission	: IEC 61034-2
Gases evolved during combustion	: IEC 60754-1: <0,5% acid gas IEC 60754-2: pH ≥4,3; conductivity ≤10 μSmm ⁻¹

Standards

Construction and Design	: IEC 60228, IEC 60092-350, IEC 60092-353
Materials	: IEC 60092-351, IEC 60092-359



HF-CXOSA 0.6/1kV

Halogen free low smoke power cables,
with copper wire braiding



No. of Cores	Conductor Size	Nominal Outer Diameter	Maximum Conductor Resistance	Voltage Test (A.C)	Minimum Insulation Resistance	Approx. Cable Weight
No.s	mm ²	mm	Ω/km-20°C	kV/5min	MΩ·km-20 °C	kg/km
1	1	6.7	18.1	3.5	1380	55
1	1.5	6.9	12.1	3.5	850	85
1	2.5	7.4	7.41	3.5	700	100
1	4	7.9	4.61	3.5	600	120
1	6	8.5	3.08	3.5	500	130
1	10	9.6	1.83	3.5	400	175
1	16	11.6	1.21	3.5	340	270
1	25	13.4	0.780	3.5	290	380
1	35	15.3	0.554	3.5	270	510
1	50	17.3	0.386	3.5	250	680
1	70	19.7	0.272	3.5	220	930
1	95	21.4	0.206	3.5	210	1190
1	120	23.4	0.161	3.5	210	1475
1	150	25.6	0.129	3.5	210	1790
1	185	28.3	0.1060	3.5	210	2210
1	240	31.4	0.0801	3.5	210	2865
1	300	34.3	0.0641	3.5	200	3515
1	400	39.2	0.0486	3.5	200	4460
2	1	9.8	18.1	3.5	1380	100
2	1.5	10.4	12.1	3.5	850	135
2	2.5	11.3	7.41	3.5	700	170
2	4	12.6	4.61	3.5	600	200
2	6	14.3	3.08	3.5	500	260
2	10	16.2	1.83	3.5	400	400
2	16	19.7	1.21	3.5	340	620
2	25	23.5	0.780	3.5	290	880
2	35	26.1	0.554	3.5	270	1130
2	50	29.9	0.386	3.5	250	1500
2	70	34.7	0.272	3.5	220	2060
2	95	39.1	0.206	3.5	210	2720
2	120	42.9	0.161	3.5	210	3270
2	150	47.3	0.129	3.5	210	3990
2	185	52.9	0.1060	3.5	210	4980
2	240	59.3	0.0801	3.5	210	6290
2	300	65.0	0.0641	3.5	200	7730
3	1	10.3	18.1	3.5	1380	115
3	1.5	10.9	12.1	3.5	850	160
3	2.5	12.1	7.41	3.5	700	200
3	4	13.2	4.61	3.5	600	260
3	6	15.0	3.08	3.5	500	335
3	10	17.2	1.83	3.5	400	510
3	16	20.8	1.21	3.5	340	800
3	25	25.1	0.780	3.5	290	1150
3	35	27.9	0.554	3.5	270	1490
3	50	32.0	0.386	3.5	250	1990
3	70	37.7	0.272	3.5	220	2860
3	95	41.8	0.206	3.5	210	3650
3	120	45.9	0.161	3.5	210	4550



HF-CXOSA 0.6/1kV

Halogen free low smoke power cables,
with copper wire braiding



No. of Cores	Conductor Size	Nominal Outer Diameter	Maximum Conductor Resistance	Voltage Test (A.C)	Minimum Insulation Resistance	Approx. Cable Weight
No.s	mm ²	mm	Ω/km·20°C	kV/5min	MΩkm·20 °C	kg/km
3	150	51.0	0.129	3.5	210	5450
3	185	56.8	0.106	3.5	210	6700
3	240	63.7	0.0801	3.5	210	8510
4	1	11.1	18.1	3.5	1380	140
4	1.5	11.9	12.1	3.5	850	185
4	2.5	13.0	7.41	3.5	700	245
4	4	14.9	4.61	3.5	600	315
4	6	16.3	3.08	3.5	500	435
4	10	18.7	1.83	3.5	400	635
4	16	22.8	1.21	3.5	340	1000
4	25	27.6	0.780	3.5	290	1460
4	35	30.7	0.554	3.5	270	1880
4	50	35.2	0.386	3.5	250	2530
4	70	41.7	0.272	3.5	220	3660
4	95	46.0	0.206	3.5	210	4895
4	120	51.2	0.161	3.5	210	5660
4	150	56.4	0.129	3.5	210	6920
4	185	63.2	0.106	3.5	210	8645
5	1	12.1	18.1	3.5	1380	165
5	1.5	12.9	12.1	3.5	850	220
5	2.5	14.9	7.41	3.5	700	285
5	4	16.1	4.61	3.5	600	270
5	6	17.9	3.08	3.5	500	380
5	10	20.6	1.83	3.5	400	795
5	16	25.1	1.21	3.5	340	1210
5	25	30.3	0.780	3.5	290	1820
5	35	33.8	0.554	3.5	270	2390
5	50	39.6	0.386	3.5	250	3230
5	70	46.0	0.272	3.5	220	4480
6	1	13.0	18.1	3.5	1380	200
6	1.5	14.6	12.1	3.5	850	245
6	2.5	16.0	7.41	3.5	700	350
7	1	13.0	19.20	3.5	1380	215
7	1.5	14.6	12.1	3.5	850	270
7	2.5	16.0	7.41	3.5	700	355
8	1	14.7	19.2	3.5	1380	235
8	1.5	15.6	12.1	3.5	850	340
8	2.5	17.3	7.41	3.5	700	440
9	1	15.6	18.1	3.5	1380	300
9	1.5	16.6	12.1	3.5	850	370
9	2.5	18.4	7.41	3.5	700	490
10	1	16.8	18.1	3.5	1380	310
10	1.5	18.1	12.1	3.5	850	395
10	2.5	20.1	7.41	3.5	700	540
12	1	17.5	18.1	3.5	1380	350
12	1.5	18.6	12.1	3.5	850	440
12	2.5	20.7	7.41	3.5	700	580



HF-CXOSA 0.6/1kV

Halogen free low smoke power cables,
with copper wire braiding



No. of Cores	Conductor Size	Nominal Outer Diameter	Maximum Conductor Resistance	Voltage Test (A.C)	Minimum Insulation Resistance	Approx. Cable Weight
No.s	mm ²	mm	Ω/km·20°C	kV/5min	MΩ·km·20 °C	kg/km
14	1	18.2	18.1	3.5	1380	390
14	1.5	19.4	12.1	3.5	850	495
14	2.5	21.6	7.41	3.5	700	670
16	1	19.1	18.1	3.5	1380	430
16	1.5	20.6	12.1	3.5	850	560
16	2.5	22.9	7.41	3.5	700	765
18	1	20.2	18.1	3.5	1380	470
18	1.5	21.5	12.1	3.5	850	590
18	2.5	24.0	7.41	3.5	700	810
19	1	20.2	18.1	3.5	1380	490
19	1.5	21.5	12.1	3.5	850	600
19	2.5	24.0	7.41	3.5	700	835
20	1	20.7	18.1	3.5	1380	510
20	1.5	22.1	12.10	3.5	850	660
20	2.5	24.6	7.41	3.5	700	910
23	1	22.0	18.1	3.5	1380	580
23	1.5	23.7	12.1	3.5	850	750
23	2.5	26.4	7.41	3.5	700	1060
24	1	23.4	18.1	3.5	1380	600
24	1.5	25.0	12.1	3.5	850	785
24	2.5	28.3	7.41	3.5	700	1095
27	1	23.8	18.1	3.5	1380	650
27	1.5	25.7	12.1	3.5	850	830
27	2.5	28.9	7.4	3.5	700	1180
28	1	23.8	18.1	3.5	1380	680
28	1.5	25.7	12.1	3.5	850	870
28	2.5	28.9	7.41	3.5	700	1210
30	1	24.6	18.1	3.5	1380	730
30	1.5	26.5	12.1	3.5	850	940
30	2.5	29.8	7.4	3.5	700	1290
32	1	25.0	18.1	3.5	1380	770
32	1.5	27.0	12.1	3.5	850	980
32	2.5	30.3	7.4	3.5	700	1340
33	1	25.6	18.1	3.5	1380	800
33	1.5	27.5	12.1	3.5	850	995
33	2.5	31.1	7.41	3.5	700	1380
34	1	25.8	18.1	3.5	1380	810
34	1.5	27.6	12.1	3.5	850	1010
34	2.5	31.4	7.41	3.5	700	1420
37	1	26.5	18.1	3.5	1380	850
37	1.5	28.8	12.1	3.5	850	1060
37	2.5	32.3	7.4	3.5	700	1530
44	1	29.9	18.1	3.5	1380	940
44	1.5	32.4	12.1	3.5	850	1290
44	2.5	36.8	7.41	3.5	700	1780