

**Ex Light fitting with protection guard brass max.
200W 230V B22, IP66/67**

WISKA 
make power smile



Remarks:

Light fittings with protection guard,
brass, 3312, up to T6, max. 200W, IP66/67
Ignition protection: de
Explosion protection:
II 2G Ex de IIC T6...T3 Gb
II 2D Ex tb IIIC T85°C...T200°C Db

Zone: 1

Certificates: TÜV 14 ATEX 7567 X
IECEx TUR 15.0022X
Lampholder: B22
Lamp: incandescent lamp up to 200W;
Fluorescent lamp up to 25W; blendend
lamp up to 160W, LED lamps up to 18W
(not included in delivery)
2 cable glands M24x1,5-Z14 -O-

WISKA-Order no.	10031257	Type of cable gland	M24x1,5 Z 14 / 12-14,5mm
Type	Ex-3312/D/B22/2x24-Z14	Material cable gland	Brass
Material	Brass	Using for cable gland	
Globe colour	Clear	Type of cable	armoured
Material guard	Brass	Ø cable diameter min	12 mm
Power [^]	max. 200 W	Ø cable diameter max	14,5 mm
Voltage	230 V	Mounting	Ceiling, Upside down, Surface mounting
Voltage max. (V)	250 V	Approval	IECEx TUR 15.0022X, TÜV 14 ATEX 7567 X
Type of Voltage	AC	Marking	II 2G Ex de IIC T6...T3 Gb, II2D Ex tbIIIC T85...T200°C Db
Frequence	50/60 Hz	Explosion Groups	IIC
Protection class	IP66 / IP67	Temp.-class	max. T6
Operational areas	Explosion protection	Zone	1, 21
Temp. range min	-40 °C	External dimensions LxWxH	244x255x310mm
Temp. range max	55 °C	Weight	14,41 kg
Lampholder	B22d		